

Security Cages



Product Overview:

The new Caging System has been designed to offer a modular solution to the issue of security within facilities where multiple users have access to the same zones. The assembly is designed to be mounted on standard computer raised floors and is offered in standard form to meet footprints of 600mm square tiles. Other tile sizes can be easily accommodated - please contact us for details.

The design allows for all but the four tiles that the vertical supports sit on to be raised, facilitating easy access to under floor cables and services. Additionally, because of their modular design the cages can be retro fitted over existing installations to compliment existing security measures.



Features:

- Designed to provide an aesthetically pleasing solution.
- Designed to compliment floor standing cabinets well as two post frame assemblies.
- The cage offers internal clearance allowing cabinets up to 2400mm high to be accommodated within the cage.
- The basic structure offers the facility for mounting internal lights and/or CCTV cameras etc.
- Side panels, rear panels and doors are available in various venting patterns to enable easy configuration to meet customer specific requirements.
- Options include:
 - Plain panels.
 - Slotted panels.
 - Lightly vented panels.
 - Fully vented panels
- For additional security between adjoining cages, side panels can only be removed if both sides of the panel are accessible.
- Various door options:-
 - Bi-fold doors (vented or plain).
 - Double sliding doors (vented or plain).



The cage system is designed to offer 3 basic foot prints

Option	Width	Depth	Height (approx)
1	1800mm	3000mm	2500mm
2	2400mm	3000mm	2500mm
3	3000mm	3000mm	2500mm

Security Cages

DOOR	DOOR	DOOR
CAGE - 1	CAGE - 3	CAGE - 5
CAGE - 2	CAGE - 4	CAGE - 6
DOOR	DOOR	DOOR

Group of 6 individual cages

The door options are designed to offer maximum access through the door apertures.

- Optional heavily vented roof panels are available.
- All doors offer secure locking facilities with 2-point locking.
- Cages can be assembled and configured back-to-back or side-to-side.
- All panel work has earth studs fitted to comply with IEC directives.
- The side walls and/or rear walls, together with the side vertical and bottom front to rear member can be removed providing unhindered walk through access from adjoining cages.

DOOR	DOOR	DOOR
DOOR	DOOR	DOOR

Divider walls removed to form 1 large cage

- The framework provides integral cable management facility allowing cabling for overhead lights to be neatly hidden.
- Cable management options enable cables to be managed from below floor to overhead.
- The cages are shipped in flat pack form for easy movement to site.
- They are designed to be installed by two operatives in approximately 1 1/2 – 2 hours.

Future Developments

- Electronic locks.
- Provision for remote monitoring.

